VD1 SEWN DUCTING HOSE





The VD1 is a lightweight, sewn single-ply PVC vinyl coated polyester duct with a spring steel wire helix & heavy-duty PVC wearstrip. For positive pressure movement of air, dust and fumes at temperatures under 180 degrees F. Not for vacuum.

Standard lengths are 25 feet, but custom lengths are available. Can be secured with optional belted cuffs or wire ropes. Flame retardant to UL94V-O rating.

STANDARD WIRE ROPE RING END

OPTIONAL BELT END

QT Y	HOSE DIA	OAL	COMPR RATIO	PRESSURE	NEGATIVE PRESS	BEND RADIUS	WEIGHT
	(in)	(in)		(psi)	(in/hg)	(in)	(Ibs/ft)
	12		12:1	7	N/A	9.0	0.9
	14		15:1	6	N/A	10.0	1
	16		15:1	5	N/A	11.0	1.2
	18		15:1	4.5	N/A	12.0	1.6
	20		15:1	3	N/A	13.0	1.7
	24		15:1	2	N/A	15.5	2

NOTES:

THE HOSE IS RATED FOR -20F TO 180F...

CUSTOMER PROJECT ENGINEER	PROJECT		HOSECRAFT		
CONTRACTOR		MODEL:	VD1		
CERTIFICATION		DRAWN BY:	SEWN DUCTING		
		PDB 3/22/24	HOSE		

HOSECRAFT USA 2315 W. HUBBARD ST, CHICAGO, IL 60611

PHONE: 800-584-4168 FAX: 312-421-6327